









At the heart of the HNTR 350 beats a fuel-injected, long-stroke 350cc J-engine that delivers a smoother ride, higher RPM and dollops of torque. Paired with a steady downtube spine frame and grounded suspension, the HNTR 350 gives the right amount of power and precision, whether you're revving up the city streets or gunning down the motorway.





The HNTR 350's retro-inspired rotary switch cubes make powering up and taking off a tactile, hands-on experience designed to wake you up.



even while navigating stop-and-go traffic.



Built for unpredictable urban environments, the anti-lock braking system with 300mm front and 270mm rear discs bring you safely to a stop at even the shortest of distances, keeping you firmly in control.



HNTR 350 VS. THE HERD



SPECIFICATIONS

ENGINE/DRIVETRAIN

Capacity Type **Fuel supply**

Cam drive Cooling

Bore (mm) Stroke (mm) **Compression ratio**

Valves Power (kW) Max power RPM **Torque (nm)** Max torque RPM Max speed **Max RPM**

Fuel economy (kmpl)

Clutch type Gears

Primary drive ratio Ist gear ratio 2nd gear ratio 3rd gear ratio 4th gear ratio 5th gear ratio 6th gear ratio

Final drive ratio **CO2**

Fuel consumption Pass by noise

349

Single cylinder, 4-stroke **Electronic fuel injection**

SOHC Air-oil cooled

75 85.8 9.5:1 15* 6100*

27*

114 km/h 7000* 36.2*

Wet multiplate

2.313 2.615 1.706 1.3 1.04 0.875 2.8 64.03 g/km

2.65 I/100 km 76.1 dB(A)

ELECTRICAL SYSTEM

CSystem voltage (V) Battery rating (Ah)

12V 8.0Ah

CHASSIS

Mass - wet (kg)

Mass - dry (kg) (Wet mass - fuel/battery)

Payload (kg) GVW (kg) Fuel capacity (L) Seat height

Ground clearance (at static sag)

Rake/head angle (deg) Trail (mm) Steering lock (deg) Wheelbase (mm) Tyre (Front)

Tyre (Rear)

Frame **Suspension (Front) Travel - (Front) (mm) Suspension (Rear)**

Travel - (Rear) (mm) **Brakes (Front)**

Brakes (Rear) ABS

181

25 @ Full droop **96.4** @ Full droop

43 1370

Alloy wheel- 110/70-17" 100/80 - 17"" - 52P(Tube Type) Alloy wheel - 140/70 - 17" - 66P (tubeless type) Twin downtube spine frame **Telescopic, 41mm forks**

130

Twin tube emulsion shock absorbers with 6-step adjustable preload

102

300 mm fixed disc with twin piston floating caliper 270 mm disc, single piston

floating caliper Type dual channel









